



## P120S Economical Supermarket Pump

The P120S is specially designed to handle condensate from supermarket refrigerated display cabinets, it is extremely easy to install and maintain. The compact design of the pump facilitates installation under low-slung display cabinets, and it removes water during the defrost cycle.

It adopts an easy-to-clean stainless tank suitable for hot water handling up to 75°C, a non-return valve, 2 inlets for option(top or side), which makes the pump effective to discharge and filtrate defrosted water.

## P120S Economical Supermarket Pump

Special Design, Simple Installation



Stainless steel case with large reservoir of 3 liters.



Ideal for cold produce display cabinets in supermarkets and convenience stores.



Low profile (69mm height) extremely easy for installation and maintenance.



Made of heat-resistant material, suitable for handling hot water up to 75°C.



120 L/h  
Max flow



30 m  
Max rec. head



3 L  
Tank capacity

### Technical Data

Model	P120S
Voltage	230 V~ / 50-60 Hz or 100-120 V~ / 50-60 Hz
Discharge Head(Max.)	30 m (98 ft)
Flow Rate(Max.)	120 L/h (32 GPH)
Tank Capacity	3 L
Sound Level at 1m	40-62 dB(A)
Water Temp.	Max 75 °C
Power	30 W
Packing	Carton: 2 pcs

### Flow Rate

