

## Single Piston Refrigerant Recovery Machine

The MRM55 is a lightweight, efficient and reliable refrigerant recovery machine. Its compact and sturdy casing provides an ideal solution for quick and easy refrigerant recovery.

Different from most brands of refrigerant recovery machines, it adopts an integrated vertical structure design with a top-mounted control knob and two pressure gauges.

In addition, there is a maintenance port on the back of the machine to facilitate the replacement of piston rings and air valve cores, bringing more user-friendly experience.

At the same time, this recovery machine meets for A2L-level refrigerants and is backward compatible with these older ones (such as R12, R22 and R410A).

## MRM55 Refrigerant Recovery Machine

Lightweight, Efficient & Reliable




Built-in oil separator (MRM55OS)



Vertical structure design based on ergonomic experience



Overhead pressure gauge for easy reading the exact data



An easy access port at the back of machine for fast maintenance

Model	MRM55 / MRM55OS				
Refrigerant	III: R12, R134A, R401C, R406A, R500, R1234yf	Automatic Safety Shut-off		38.5 bar / 3850 kpa (558 psi)	
	IV: R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509	III	IV	V	
	V: R402A, R404A, R407A, R407B, R410A, R507, R32	Vapor	0.22 kg/min	0.25 kg/min	0.25 kg/min
Recovery Rate	Voltage	Liquid	1.8 kg/min	2.0 kg/min	2.2 kg/min
		Push/Pull	5.0 kg/min	6.0 kg/min	6.5 kg/min
Motor Power	100-120 V~ / 50-60 Hz	230V~ / 50-60 Hz	Operating Temperature		0 °C - 40 °C
Motor Speed	3/4 HP		Dimensions		259mm(L)*235mm(W)*390mm(H)
Current(Max.)	2300 RPM		Weight		9.5 kg
Compressor	8A	4A	Packing		Carton: 1 pc
	Oil-less, Air-cooled, Piston-style				

### Accessories



1.8m power cord



Filter



Shoulder Strap



Hose