



## Dual Pistons Refrigerant Recovery Machine

The MRM75 is an efficient and reliable refrigerant recovery machine with a compact and sturdy casing. Its dual-piston design provides an ideal solution for fast and efficient refrigerant recovery.

Different from most brands of refrigerant recovery machines, it adopts the design of mounting control knob and pressure gauges on the top. In addition, there is a maintenance port on the back of the machine to facilitate the replacement of piston rings and gas valve cores, bringing a more user-friendly experience.

At the same time, the recovery machine meets for A2L-level refrigerants and is backward compatible with these older ones (such as R12, R22 and R410A).

## MRM75 Refrigerant Recovery Machine

Fast Recovery, Efficient & Reliable



Built-in oil separator (MRM75OS)



Oil-free compressor with high efficient



Overhead digital display for easy reading the exact data



An easy access port at the back of machine for fast maintenance

Model	MRM75 / MRM75OS					
Refrigerant	III: R12, R134A, R401C, R406A, R500, R1234yf	Automatic Safety Shut-off		38.5 bar / 3850 kpa (558 psi)		
	IV: R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509	Recovery Rate	III	IV	V	
	V: R402A, R404A, R407A, R407B, R410A, R507, R32	Vapor	0.5 kg/min	0.7 kg/min	0.7 kg/min	
Voltage	100-120V~ / 50-60 Hz	230 V~ / 50-60 Hz	Liquid	2.6 kg/min	3 kg/min	3.9 kg/min
Motor Power	1.3HP		Push/Pull	8.2 kg/min	9.3 kg/min	10.5 kg/min
Motor Speed	3000RPM		Operating Temperature	0 °C - 40 °C		
Current(Max.)	13A	6.5A	Dimensions	386mm(L)*255mm(W)*276mm(H)		
Compressor	Oil-less, Air-cooled, Piston-style		Weight	11.6 kg		
			Packing	Carton:1 pc		

### Accessories



1.8m power cord



Filter



Shoulder Strap



Hose